

GBT 3098. 13-1996紧固件机械性能 螺栓与螺
钉的扭矩试验和破坏扭矩公称直径1-10mm

螺纹规格	螺距 mm	最小破坏扭矩				螺纹规格	螺距 mm	最小破坏扭矩			
		性能等级						性能等级			
		8.8 级	9.8 级	10.9 级	12.9级			8.8 级	9.8 级	10.9 级	12.9级
M1	0.25	0.033	0.036	0.04	0.045	M5	0.8	7.6	8.3	9.3	10
M1.2	0.25	0.075	0.082	0.092	0.1	M6	1	13	14	16	17
M1.4	0.3	0.12	0.13	0.14	0.16	M7	1	23	25	28	31
M1.6	0.35	0.16	0.18	0.2	0.22	M8	1.25	33	36	40	44
M2	0.4	0.37	0.4	0.45	0.5	M8×1	—	38	42	46	52
M2.5	0.45	0.82	0.9	1	1.1	M10	1.5	66	72	81	90
M3	0.5	1.5	1.7	1.9	2.1	M10×1	—	84	92	102	114
M3.5	0.6	2.4	2.7	3	3.3	M10×1.25	—	75	82	91	102
M4	0.7	3.6	3.9	4.4	4.9						